HDMI (HDBaseT) CAT5 Extender Series ITEM NO.: HE02EI HDMI & IR CAT5 Extender Over Single CAT5 Cable

HE02EI HDMI (HDBaseT) CAT5 Extender is using only one cost effective CAT5e/6 cable to extend your HDTV display up to 60 meters at 1080p, 70 meters by CAT6a cable. With IR function to delivers significant value to the entire home and commercial entertainment system.



Features:


• Extends HDMI and IR signal over one CAT5/5e/6 cable.

- Uncompressed high definition video up to 1080p@60Hz@48bits and 3D and 4K*2K capable.
- Built in IR control, IR signal could be selectable at either TX/RX side.
- Max. Data Rate- 10.2Gbps.
- HDMI 1.4 and HDCP compliance.
- Transmission range up to 60M by CAT5e/6, 70M by CAT6a cable at 1080p@60Hz@24bit.
- Audio support up to LPCM7.1 , Dolby TrueHD , DTS-HD MA.

Installation view:



Panel view:



IR Switch Setting:

- **1.** When use BD/DVD remote controller (DVD at remote side), HE01EIR IR switch move to RX and connect with Receiver cable; HE01EIT IR switch move to TX and connect with Emitter cable.
- 2. When use TV remote controller (TV at remote side), HE01EIT IR switch move to RX and connect with Receiver cable; HE01EIR IR switch move to TX and connect with Emitter cable.

Cable:

Link cable recommend use high quality Cat.5e
Cat.6, CAT6a UTP / STP or FTP cable.

Transmission Distance:

The maximum transmission distance up to 60M by CAT5e/6, 70M by CAT6a cable (1080p / 60Hz / 24 bits), and use lower resolution won't extend longer distance.

If connection through the wall socket, the cable length must less 5 meters between HDMI extender and wall jack, as below drawing:

	— CAT.6a 1080p 70m (Max) —	
Transmitter MAX 5M		Wall Jack MAX 5M Receiver

RJ45 Define:

Video Link (TIA/EIA-568-B)

1. Orange-white	DATA0 +
2. Orange	DATA0 -
3. Green-white	DATA1 +
4. Blue	DATA2 +
5. Blue-white	DATA2 -
6. Green	DATA1 -
7. Brown-white	DATA3 +
8. Brown	DATA3 -

LED Indication:

Power Link	GREEN BLUE	On Flash	(power) (under linking)	
		On	(linking)	
		Off	(under linking or cable no connect)	

Caution:

1.The wiring must away from any equipment with electromagnetic wave, i.e.: mobile phone, microwave, radio equipment, fluorescent lamp, power lines.

2. This device is not network equipment, do not connect with Network to avoid damage.

HE02EI Package Include:

HE02EIT HDM Transmitter x 1 pcs HE02EIR HDMI Receiver x 1 pcs IR Emitter Cable x 1 pcs IR Receiver Cable x 1 pcs Mounting Screw pack x 2 bags Power Adapter x 1 pcs

Specification:

ITEM NO.		HE02EIT	HE02EIR		
Resolution		Up to 1080p / 60Hz / 48 bit			
Distance		60M by CAT5e/6, 70M by CAT6a			
HDMI Connector		Туре А			
IR Carrier Freque	ncy	30-60Khz			
IR Angle		±30	±55		
IR Distance		5m			
Power Supply		Regulated DC5V 2A			
Power Consumpti	ver Consumption 380mA (Max) 820mA (Max)				
Temperature		Operation: 0 to 55° C, Storage: -20 TO 85° C, Humidity: up to 9			
Dimensions	mm	49 x 92.3 x 25			
Weight	g	125 135			

Rohs (EFC C

Rev. B